

Portable Thermal Printer

TM-80C

- Multiple 1D & 2D barcode printing
- Support 80mm&58mm paper width
- NV LOGO download and printing
- Support IAP update online
- Support order reminder and error alarm
- Saving power function



| Printing Features | |
|----------------------------|--|
| Print method | Direct Thermal |
| Max.print width | 72 mm |
| Print density | 576 dots/line |
| Print speed | MAX 70mm/s |
| Print head | 50 km |
| Media | |
| Paper thickness | 0.06 mm ~0.08 mm |
| Label Width | 79.5±0.5 mm |
| Label roll diameter | 50 mm |
| Performance Features | |
| Input buffer | 128K bytes |
| NV Flash | 4M bytes |
| Interface | USB+Bluetooth |
| Fonts/Graphics/Symbologies | |
| Character size | ANK, Font A: 12×24 dots Font B: 9×17 dots simplified/traditional Chinese: 24x24 dots |
| Hard character Library | Gb18030 character Library |
| 1D barcode | UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128 |
| 2D barcode | QRCODE/PDF417 |
| Physical Features | |
| Dimension | 135(D) x 105(W) x61.5(H)mm |
| Weight | 0.3 kg |
| Software | |
| Driver | Windows /Linux / iOS / Android |
| SDK | Windows / iOS / Android |
| Power supply | |
| Input | DC 5V/2A |
| Output | 7.4V / 2A |
| Environmental Conditions | |
| Operation | 0 ~ 45°C , Humidity: 10~ 85% non-condensing |
| Storage environment | -10 ~ 60°C , Humidity:10 ~ 90% non-condensing |

