



TM-80M

Portable Thermal Printer

BLUETOOTH CONNECT

WINDOWS / ANDROID / IOS

ITEM		Parameter
Printing	Printing method	Thermal dot line printing
	Resolution	203dpi, 8dots/mm
	Printing speed (Max)	70mm/s
Printing	Width	80mm
	Valid printing width	72mm
	Paper roller diameter	≤50mm
	Paper thickness	60~80μm
	Loading	Easy loading mechanism
Interface		Bluetooth and USB
Command sets		Compatible with ESC/POS
Character Set	Font	ASCII:9×17,12×24; Multiple code pages support
Barcode Symbologies	1D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D	QR code
Graphics		Support bitmap printing with different density and user defined bitmap printing (Max. 40K for per bitmap, and Max. 64K for total)
Detection	Sensors	Paper out/ low battery
Charging	Charger	5V/1A adapter
	Battery	2000mAh/7.4V rechargeable Li-ion battery. Full charge can print 300~350m (printing density not more than 12.5%) or 250~300mm (printing density not more than 25%)
Physical characteristics	Working condition	-10°C~70°C, 20%~85%RH
	Storage condition	-10°C~70°C, 20%~85%RH
	Dimension	110*122.9*67.8mm (W*D*H)
	Weight (printer only)	362g (without paper roll and with battery)
Software	Emulation	ESC/POS compatible command set
	Driver	Windows XP//Win7/Win8/Win10

